



www.safewalker.com

AUTONOMY

DAILY LIFE
ERGONOMIC
MOBILITY
HELP

SUPPORT

CONFIDENCE
SAFETY

WALK

RESULTS

RE-EDUCATION
PLAY

MOVEMENTS

INNOVATION



Our **innovation**: an alternative between a walker and a wheelchair. SAFEWALKER is a medical device of help to the walking in discharge situation. The user's weight discharge is quantifiable and adjustable, by controlling the reduction settings.

It is addressed to every person presenting walking deficiencies, temporary or permanent. This is a real 'relieve' of walking, thought for a use in total autonomy with no one's help.

The user is then going to determine the percentage of his body weight of which he wants the device to relieve him from, **in a autonomous way** by a touch-sensitive screen.

Throughout the development of the **SAFEWALKER**, safety was the main concern, indeed the posterior doors are provided with sensors authorizing the functioning of the device only when closed. The patient can not fall, the use of the **SAFEWALKER is then, totally safe.**



The **SW** is an innovating walking device based on releasing the user from his weight. It's quantifiable by a strain gauge, adjusted by a positioning cylinder.

One of SW strongest point is the possibility of making the difference between right and left of the user's discharge, in real time by it's walking cylinder and sensors.

📏 DIMENSIONS

| <i>cm / inches</i> | Folded | Unfolded |
|--------------------------|--------------------|--------------------|
| Height saddle | 40 / 15.74 | 100 / 43.30 |
| Lenght frame | 100 / 39.37 | 115 / 45.27 |
| Height of the body guard | 75 / 29.52 | 155 / 61.02 |
| Width | 58 / 22.83 | 58 / 22.83 |

📏 WEIGHT

- Weight of SW: **38 Kg / 83.6 Lbs**
- Maximum weight of the user: 120 Kg / 264 Lbs
(possibility to order for heavier persons)

📏 STANDARD

EC Standard, medical dispositif of class 1, 93/42/EEC

📏 PI

Certificat delivered, August 9th , 2013 # 10 04492, France , Europe, USA, Canada, Australia

- 2 dorsal supports adjustable forward / backward 25 cm (9.8 inches)
- 2 handles
- Touch-sensitive screen
- Adjustable lap support in height 15 cm (5.9 inches)
- 2 adjustable side supports
- Positioning jack allowing to lower the saddle at the level of a chair, or toilet seat about 40 cm (15.7 inches) from the ground and rise up to standing position
- Adjustable saddle in height: 18 cm (7.1 inches) front / back: 15 cm (5.9 inches)
- 4 free wheels; the 2 rear ones can be blocked in unidirectional
- Front brakes: downward position parking brake: for installation and deinstallation progressive brakes: upward position
- work on refillable independent batteries (2x12v) by a side grip on sector (220v) approximately time of load: **6 hours**
- Variable duration according to the use (given **per day in intensive use**)
- Fits into a car trunk
- Color of frame on request
- Saddlery and supports on request

Posterior doors



Positioning jack

Touch-sensitive screen

➤ OPTIONS

- Electric brakes with commands on the touch-sensitive screen
- Dorsal and lap supports lengths
- Lithium batteries



www.safewalker.com

Contact

We are at your disposal!

116 Route d'Espagne, Hélios 5, 31100 TOULOUSE - France

CEO: Hervé Escourrou

Tel: 0608427375

Email: h.escourrou@safewalker.com

Sales manager: Jérémie Moles

Tel.: 06 75 51 09 36

Email: j.moles@safewalker.com